



In the United States Patent and Trademark Office

Applicant: Jens-Uwe Gleu

Attorney Docket: 202-114

Patent Application  
Serial No: 10/724,759

Filed: December 2, 2003

For: Air Spring Cover and Method  
of Making the Same

Statement by Attorney that Papers Attached to  
Declaration are a Copy of those Filed in the Patent  
and Trademark Office to Get a Filing Date

Commissioner for Patents and Trademarks  
P.O. Box 1450  
Alexandria, Virginia 22313-1450

Dear Sir:

I, Walter Ottesen, state that I am the attorney for this application and that I have reviewed and found the specification (pages 1 to 9) and one sheet of drawing (FIGS. 1 and 2) as shown in my files to be the papers attached to the declaration of Jens-Uwe Gleu for Air Spring Cover and Method of Making the Same which accompanies this statement and I declare that these papers attached to the declaration are a true copy of the specification and any amendment thereto which I filed in the Patent and Trademark Office in order to obtain a filing date for this application on December 2, 2003.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so

made are punishable by fine or imprisonment, or both, under  
Section 1001 of Title 18 of the United States Code and that such  
willful false statements may jeopardize the validity of the application  
or any patent issued thereon.

Respectfully submitted,

A handwritten signature in black ink, appearing to read "Walter Ottesen". The signature is fluid and cursive, with the first name "Walter" and last name "Ottesen" clearly distinguishable.

Walter Ottesen  
Reg. No. 25,544

Walter Ottesen  
Patent Attorney  
P.O. Box 4026  
Gaithersburg, Maryland 20885-4026

Phone: (301) 869-8950

Date: December 19, 2003



Air Spring Cover and Method of Making the Same

Field of the Invention

5 The invention relates to an air spring whose cover has an additional volume and a method for making the air spring.

Background of the Invention

10 A large volume in a given space available for mounting a component as well as the ensurance of accessibility is often difficult to realize without complicated air spring cover geometries having deep undercuts. Such an air spring cover can, as a rule, be realized by a partition in the transverse direction by two shells which must then be connected to each other air-tight and with high strength. The shells can, for example, be made by deep drawing. The invention is related to a cost effective, air-tight and high-strength connection of the deep-drawn half-shells.

20 The practice to date for connecting shell-shaped housing parts provides for a gas-tight welding or gluing with a subsequent helium leakage test. Welding or gluing as well as the subsequent leakage test is too complex for the manufacture of a mass produced article.

25 United States Patent 4,659,070 describes an air spring suspension with a shock absorber and a primary air spring chamber which is assigned a further air chamber. The cylindrical housing parts are welded to each other over the entire peripheral region as described at column 3, starting at line 1.

30 United States Patent 4,616,811 describes an air spring which likewise comprises a primary air chamber and an ancillary air chamber. Here too, the different cylindrical housing parts are welded to each other as described at column 3, starting at

line 8.

In German patent publication 1,039,375 (corresponding to United States patent application serial no. 521,031, filed July 11, 1955), an air spring is described for suspending motor vehicles. The cap-shaped parts of this suspension are welded to each other along the edge.

The air spring disclosed in United States Patent 2,893,104 has a large volume. The edge of the vessel has a welded seam.

An air spring and shock absorber assembly is described in United States Patent 6,237,902 having upper and lower parts which are welded to each other around the periphery.

In United States Patent 3,700,225, an air spring and shock absorber assembly is disclosed wherein the housing and air spring cover are welded to each other.

From the above, it can be seen that the conventional method in air spring technology comprises making a weld seam for pressure-tight connecting different housing parts.

#### Summary of the Invention

It is an object of the invention to provide an air-tight and high-strength connection of two air spring cover half-shells in a cost effective manner. The half-shells are especially deep drawn half-shells.

The air spring of the invention includes: an air spring cover; a rolling-lobe flexible member attached to the air spring cover; the air spring cover including an upper part and a lower part delimiting an extra volume of the air spring; the upper and lower parts conjointly defining an interface whereat the parts are joined to each other; and, a pressure-tight and high-strength flanged seam formed at the interface.

Thus, according to a feature of the invention, the two parts

are tightly connected to each other with a bent-over flange connection.

According to another feature of the invention, the parts, which are to be connected to each other, are tightly joined to each other by bending over a clamp made of a plastically deformable material. The clamp can, for example, be a steel ring.

The individual shells (the upper part and the lower part) can be manufactured by separate and optimized manufacturing methods such as by deep drawing, injection molding and casting.

An elastomeric part such as an O-ring can be inserted in the flanged seam itself or between the contact surfaces of the half-shells to improve an air-tight seal. With a suitable configuration of the elastomeric insert part, the connection can be used for insulating from vibrations.

The geometry of the parts, which are to be connected, need not be circular at the connecting interface; rather, the parts can be elliptical or can be otherwise configured.

The two half-shells can be made of different materials. The shells can also be made of a material which is not plastically deformable.

The bent-over clamp can be a purely cylindrical ring in the condition before mounting or the clamp can have a cross section which is already preformed to be concave. The flanged connection can be carried out very rapidly and cost effectively with an axial-forming process (press) or by a series of axial-forming processes. The flange connection can also be carried out by rolling.

In total, a cost effective manufacturing process results. A follow-up tightness check is not needed, that is, a considerable

cost advantage is associated with the method of the invention. The method of the invention can be applied anywhere where hollow bodies are made which can be easily manufactured with the hollow body being partitioned.

5     Brief Description of the Drawings

The invention will now be described with reference to the drawings wherein:

FIG. 1 is a side elevation view, in section, of an air spring cover chamber wherein the edge of the upper shell to be flange connected is folded over; and,

10

FIG. 2 is a side elevation view, in section, of another embodiment showing an air spring cover wherein a separate clamp is flange connected at the interface of the upper and lower parts of the air spring cover.

15     Description of the Preferred Embodiments of the Invention

An air spring includes a defined air spring volume which is closed air-tight by a cover 2, a rolling-lobe flexible member 9 and a roll-off piston (not shown). The rolling-lobe flexible member 9 is attached to the cover 2 by a clamp ring 7. In order to configure the suspension performance more comfortably, air springs are increasingly equipped with an additional volume 4. This additional volume 4 is disposed, for example, in the region of the air spring cover 2. For this purpose, the air spring cover 2 is made of two half-shells (2a, 2b) which function as a housing for the wanted additional volume 4. What is essential to the invention is the air-tight and high strength connection of the two half-shells (2a, 2b) to each other. These half-shells can be manufactured, for example, by deep drawing.

20

25

FIGS. 1 and 2 each show an air spring cover 2 comprising two half-shells (upper part 2a, lower part 2b). The two

30

shells (2a, 2b) enclose additional volume 4. According to the invention, the two parts (2a, 2b), which are to be connected, are tightly connected to each other by a flanging operation.

In the embodiment of the air spring additional volume 4 shown in FIG. 1, the edge of the upper shell 2a, which is to be flanged, is folded over. Furthermore, the upper shell 2a includes an annular depression for accommodating an O-ring 8. The flanged edge of the lower shell 2b engages over the folded-over edge of the upper shell 2a as well as the O-ring 8. For example, by rolling, a pressure-tight and tension-tight connection of the two shells (2a, 2b) to each other is formed which then defines the additional volume 4.

In the alternate embodiment shown in FIG. 2, the upper part 2a and the lower part 2b are made of materials which permit another type of connection such as with threaded fasteners. The clamp 10 is bent-over to tightly connect the upper and lower parts (2a, 2b) with each other. The clamp 10 is made of a plastic deformable material and can, for example, be a steel ring. One of the contact surfaces of the half-shells (2a, 2b) includes a recess for accommodating an O-ring 8.

It is understood that the foregoing description is that of the preferred embodiments of the invention and that various changes and modifications may be made thereto without departing from the spirit and scope of the invention as defined in the appended claims.